

View Online at <https://aerobasegroup.com/nsn/5910-00-727-4679>

**Thread Class:**

2a

**Body Style:**

Piston

**Overall Length:**

1.312 inches

**Terminal Length:**

2.000 inches

**Bushing Diameter:**

Between 0.191 inches and 0.195 inches

**Shaft Diameter:**

0.190 inches single shaft

**Bushing Length:**

0.500 inches

**Shaft Length:**

0.500 inches single shaft

**Body Length:**

Between 0.780 inches and 0.844 inches

**Overall Diameter:**

Between 0.307 inches and 0.317 inches

**Temperature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:**

-75.0/+75.0 single section

**Terminal Diameter:**

0.025 inches

**Quality Factor At 25 Deg Celsius:**

500.0

**Fragility Factor:**

Moderately rugged

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Encapsulated

**Adjustment Device Torque:**

Between 1.000 inch-ounces and 8.000 inch-ounces

**Bushing Shape:**

Round w/flat

**Insulation Dc Resistance At 25 Deg Celsius:**

1000000.0 megohms

**Bushing Width:**

Between 0.171 inches and 0.175 inches

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thread Size:**

0.190 inches

**Shaft Type:**

Round, slotted single shaft

**Capacitance Range In Picofarads:**

+0.7/+12.0 single section

**Nonderated Voltage Rating And Type:**

1250.0 dc continuous single section

**Adjustment Device Drive Type And Quantity:**

1 shaft

**Material:**

Glass capacitive electrode

**Terminal Type And Quantity:**

1 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A096a0