

View Online at <https://aerobasegroup.com/nsn/5910-00-728-1597>

Body Style:

Pellet type, w/o mtg tabs

Reliability Indicator:

Not established

Body Diameter:

0.297 inches

Mounting Slot Width:

0.050 inches

Body Length:

0.188 inches

Terminal Height From Body:

0.297 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

End Application:

Virginia class dgn (41); forrestal class cv; arleigh burke class ddg; oliver perry class ffg; wasp class lhd; seawolf class ssn; spruance class dd (9630; tarawa class lha; sturgeon class ssn (637)

Capacitance Value Per Section:

1000.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-75.0/+75.0 without voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

+0.00/+100.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

100000.0 megohms

Power Factor At Reference Temperature In Percent:

2.0000

Quality Factor At Reference Temp:

50.0000

Terminal Surface Treatment:

Solder

Special Features:

Weapon system essential

Terminal Type And Quantity:

1 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0