Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-728-5182

## **Body Style:**

W/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not established

## **Terminal Length:**

1.625 inches

#### **Body Diameter:**

0.782 inches

#### **Body Length:**

2.188 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Features Provided:**

Hermetically sealed case

## Insulation Resistance At Maximum Operating Temp:

100.0 megohms

# **Capacitance Value Per Section:**

0.150 microfarads single section

# Nonderated Operating Temp:

Between -65.0 degrees celsius and 65.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

120.0 single section

## **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:**

-50.0/+50.0 single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

## Insulation Resistance At Reference Temp:

40000.0 megohms

## **Dissipation Factor At Reference Tempurature In Percent:**

0.1000

#### **Terminal Surface Treatment:**

Solder

# **Special Features:**

200.0 volts dc nonderated continuous voltage rating

# **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

# **Demilitarization:**

No

# NSN 5910-00-728-5182

Plastic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

