NSN 5910-00-728-6013

Mica Dielectric Fixed Capacitor - Page 1 of 2



| view Online at https://aerobasegroup.com/hsh/5910-00-726-6013 |
|--|
| Body Style: |
| W/mtg tabs/flanges, terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.100 inches |
| Body Length: |
| 2.250 inches |
| Body Width: |
| 1.430 inches |
| Body Height: |
| 0.375 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.145 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 2.188 inches |
| Schematic Diagram Designator: |
| Feedthrough |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.750 inches |
| Mounting Facility Type And Quantity: |
| 4 unthreaded mounting holes |
| Capacitance Value Per Section: |
| 2700.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 3000.0 dc single section |
| Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: |
| -5.0 to 5.0 single section |
| Tolerance Range Per Section: |
| -0.00 to 10.00 percent single section |
| Case Material: |
| Plastic |
| Terminal Surface Treatment: |
| |
| Silver |
| Silver Terminal Type And Quantity: |
| |
| Terminal Type And Quantity: |
| Terminal Type And Quantity: 1 tab, solder lug |

NSN 5910-00-728-6013

Mica Dielectric Fixed Capacitor - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A010b0