NSN 5910-00-728-6915

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-728-6915
Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
Between 1.500 inches and 2.500 inches
Body Length:
Between 0.671 inches and 0.733 inches
Body Width:
Between 0.230 inches and 0.250 inches
Body Height:
Between 0.350 inches and 0.370 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
0.047 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 65.0 degrees celsius
Between -55.0 degrees celsius and 65.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:
•
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 microfarads single section
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 microfarads single section Case Material:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 microfarads single section Case Material: Metal
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 microfarads single section Case Material: Metal Insulation Resistance At Reference Temp:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 microfarads single section Case Material: Metal Insulation Resistance At Reference Temp: 500.0 megohm-microfarads
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 microfarads single section Case Material: Metal Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Case Insulation Material:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 microfarads single section Case Material: Metal Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Case Insulation Material: Plastic
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 microfarads single section Case Material: Metal Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Case Insulation Material: Plastic Terminal Type And Quantity:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 microfarads single section Case Material: Metal Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 microfarads single section Case Material: Metal Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 microfarads single section Case Material: Metal Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 microfarads single section Case Material: Metal Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section: -10.00/+10.00 microfarads single section Case Material: Metal Insulation Resistance At Reference Temp: 500.0 megohm-microfarads Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:

A010b0