## NSN 5910-00-730-0788

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-730-0788
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Diameter:
0.312 inches
Body Length:
0.812 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Internal Electrical Connection Type:
Extended foil
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
40000.0 megohm-microfarads
Capacitance Value Per Section:
43000.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
-120.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
30.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-30.0/+30.0 single section
Tolerance Range Per Section:
-1.00/+1.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
100000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
0.1000
Terminal Surface Treatment:
Solder
Dielectric Material:
Plastic polystyrene
Terminal Type And Quantity:

2 uninsulated wire lead

## NSN 5910-00-730-0788

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf	Lite:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0