NSN 5910-00-731-1358

Quartz Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-731-1358
Thread Class:
2a
Body Style:
Piston
Bushing Diameter:
0.190 inches
Bushing Length:
0.281 inches
Body Length:
0.547 inches
Overall Diameter:
0.312 inches
Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:
+0.0/+50.0 single section
Quality Factor At 25 Deg Celsius:
1500.0
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Encased
Adjustment Device Torque:
Between 1.000 inch-ounces and 10.000 inch-ounces
Bushing Shape:
Round w/flat
Insulation Dc Resistance At 25 Deg Celsius:
100.0 gigohms
Bushing Width:
0.167 inches
Mounting Facility Type And Quantity:
1 threaded bushing
Nonderated Operating Temp:
Between -55.0 degrees celsius and 150.0 degrees celsius
Thread Size:
0.190 inches
Capacitance Range In Picofarads:
+0.6/+5.5 single section
No. 1

Nonderated Voltage Rating And Type:

750.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.01 single section

NSN 5910-00-731-1358

Quartz Dielectric Variable Capacitor - Page 2 of 2



Test Data Document:

81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity

1 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A096a0