

View Online at <https://aerobasegroup.com/nsn/5910-00-733-4372>

**Body Style:**

Button type, w/mtg tabs

**Reliability Indicator:**

Not established

**Body Diameter:**

0.650 inches

**Body Length:**

0.094 inches

**Schematic Diagram Designator:**

Feedthrough

**Insulation Resistance At Maximum Operating Temp:**

15000.0 megohms

**Capacitance Value Per Section:**

2200.000 picofarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

500.0 dc single section

**Temperature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:**

-20.0 to 100.0 single section

**Tolerance Range Per Section:**

-2.00 to 2.00 percent single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

50000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

0.0010

**Terminal Surface Treatment:**

Silver

**Test Data Document:**

81349-mil-c-10950/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0