NSN 5910-00-738-8584



Plastic Dielectric Fixed Capacitor - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5910-00-738-8584
Body Style:
W/thd mtg hol (s)/stud(s) terminal(s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.500 inches
Body Length:
3.500 inches
Body Width:
1.380 inches
Body Height:
3.310 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
3.000 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Mounting Facility Screw Thread Series Designator:
Unc
Mounting Facility Type And Quantity:
2 threaded mounting studs
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
10.0 megohm-microfarads
Capacitance Value Per Section:
0.330 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.164 inches
Nonderated Continuous Voltage Rating And Type Per Section:

3000.0 dc single section

Tolerance Range Per Section:

-7.00/+7.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

18000.0 megohms

Terminal Surface Treatment:

Solder

Dielectric Material:

Plastic

NSN 5910-00-738-8584

Fiig: A010b0

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Case Insulation Material:
Plastic
Test Data Document:
07765-101-b719 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
2 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No