## NSN 5910-00-739-7738

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-739-7738 **Body Style:** W/o mtg facilities, radial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Diameter:** 0.312 inches **Body Length:** 0.156 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.250 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **End Application:** Nimitz class cvn, kidd class ddg, virginia class cgn (41), spruance class dd (963), ticonderoga class cg (47), oliver perry class ffg, forrestal class cv, los angeles class ssn (688), sturgeon class ssn (637) **Capacitance Value Per Section:** 100.000 picofarads single section **Voltage Tempurature Limits Per Section In Percent Capacitance Change:** -56.0/+22.0 without voltage applied single section **Nonderated Operating Temp:** Between 10.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1000.0 dc single section **Criticality Code Justification:** Feat **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material: Plastic Special Features:** Weapon system essential **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5910-00-739-7738

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0