## NSN 5910-00-739-7740

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-739-7740 **Body Style:** W/o mtg facilities, radial terminals Reliability Indicator: Not established **Terminal Length:** 1.250 inches **Body Diameter:** 0.156 inches **Body Length:** 0.300 inches **Center To Center Distance Between Terminals Parallel To Diameter:** Between 0.230 inches and 0.270 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **End Application:** Emory s. Land class as, general purpose electronic test equipment (gpete), Igm-30 minuteman missle. **Capacitance Value Per Section:** 220.000 picofarads single section Voltage Tempurature Limits Per Section In Percent Capacitance Change: -4.7/+4.7 without voltage applied single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1000.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 10000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 2.0000 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5910-00-739-7740

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0