Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-739-7953

#### **Body Style:**

W/o mtg facilities, axial terminals

### **Reliability Indicator:**

Not established

## Terminal Length:

1.500 inches

### **Body Diameter:**

0.312 inches

#### **Body Length:**

1.000 inches

### **Terminal Diameter:**

0.025 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### Anode Type:

Plain foil

#### **Electrical Polarization:**

Polarized

#### **Features Provided:**

Hermetically sealed case

### Capacitance Value Per Section:

1.200 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Dc Leakage At Maximum Operating Temp:

50.0 microamperes

### Nonderated Continuous Voltage Rating And Type Per Section:

250.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### Case Material:

Metal

## **Capacitive Electrode Material:**

Tantalum

# Power Factor At Reference Tempurature In Percent:

6.0000

# Dc Leakage At Reference Temp:

10.000 microamperes

# **Terminal Surface Treatment:**

Solder

# Case Insulation Material:

Plastic

Electrolytic Fixed Capacitor - Page 2 of 2



# Terminal Type And Quantity:

2 insulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0