

View Online at https://aerobasegroup.com/nsn/5910-00-752-4254

# **Body Style:**

W/thd mtg studs, axial terminals

# **Reliability Indicator:**

Not established

# **Terminal Length:**

1.625 inches

# **Body Diameter:**

0.312 inches

#### **Body Length:**

1.125 inches

### **Terminal Diameter:**

### 0.025 inches

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.625 inches

# Schematic Diagram Designator:

No common or grounded electrode (s)

# Mounting Facility Screw Thread Series Designator:

Unc

# Mounting Facility Type And Quantity:

2 threaded mounting studs

# **Features Provided:**

Hermetically sealed case

# Insulation Resistance At Maximum Operating Temp:

10.0 megohm-microfarads

### Capacitance Value Per Section:

0.150 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Thread Size:

0.138 inches

### Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

### **Case Material:**

Metal

# Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

### Power Factor At Reference Tempurature In Percent:

1.0000

# **Terminal Surface Treatment:**

Solder



Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0