NSN 5910-00-752-4255

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-752-4255

В	ody Style:
W	/thd mtg studs, axial terminals
Re	eliability Indicator:
No	ot established
Te	erminal Length:
1.0	625 inches
В	ody Diameter:
0.	562 inches
В	ody Length:
1.	125 inches
Te	erminal Diameter:
0.0	032 inches
Di	stance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.0	625 inches
So	chematic Diagram Designator:
No	common or grounded electrode (s)
In	ternal Electrical Connection Type:
Ex	ktended foil
M	ounting Facility Screw Thread Series Designator:
Ur	nc
M	ounting Facility Type And Quantity:
2 1	threaded mounting studs
Fe	eatures Provided:
Не	ermetically sealed case
In	sulation Resistance At Maximum Operating Temp:
10	0.0 megohm-microfarads
Ca	apacitance Value Per Section:
0.	180 microfarads single section
No	onderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.138 inches

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Range Per Section:

-5.00 to 5.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

20000.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

1.0000

NSN 5910-00-752-4255
Paper Dielectric Fixed Capacitor - Page 2 of 2



Terminal Surface Treatment:	
Solder	
Case Insulation Material:	
Plastic	
Terminal Type And Quantity:	
2 uninsulated wire lead	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	

A010b0