Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-752-4885

# **Body Style:**

W/mtg tabs/flanges, terminal (s) on one surface

# **Reliability Indicator:**

Not established

# **Body Length:**

1.812 inches

#### **Body Width:**

1.000 inches

#### **Body Height:**

0.750 inches

### **Unthreaded Mounting Hole Diameter:**

0.188 inches

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.125 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

# Mounting Facility Type And Quantity:

2 unthreaded mounting holes

## **Features Provided:**

Hermetically sealed case

## Insulation Resistance At Maximum Operating Temp:

10.0 megohm-microfarads

#### Capacitance Value Per Section:

0.250 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

#### **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

#### **Case Material:**

Metal

# Insulation Resistance At Reference Temp:

18000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

1.0000

## **Terminal Surface Treatment:**

Solder

### **Test Data Document:**

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 tab, solder lug

Paper Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0