NSN 5910-00-754-6787

Body Style:

Electrolytic Fixed Capacitor - Page 1 of 2

W/thd mtg hol (s)/stud(s) terminal(s) on one surface



View Online at https://aerobasegroup.com/nsn/5910-00-754-6787

| Reliability Indicator: |
|--|
| Not established |
| Body Length: |
| 0.705 inches |
| Body Width: |
| 0.500 inches |
| Body Height: |
| 0.705 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 0.859 inches |
| Schematic Diagram Designator: |
| Electrod (s) grounded to case |
| Anode Type: |
| Etched foil |
| Electrical Polarization: |
| Polarized |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Mounting Facility Type And Quantity: |
| 2 threaded mounting studs |
| Features Provided: |
| Hermetically sealed case |
| Capacitance Value Per Section: |
| 30.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Thread Size: |
| 0.138 inches |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc single section |
| Tolerance Range Per Section: |
| -15.00/+75.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Tantalum |
| Terminal Type And Quantity: |
| 1 tab, solder lug |
| Shelf Life: |
| N/a |

NSN 5910-00-754-6787

Electrolytic Fixed Capacitor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0