NSN 5910-00-754-7116

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-754-7116

Body Style:
W/thd mtg hole/stud, terminal (s) on one end
Reliability Indicator:
Not established
Width Across Flats:
0.250 inches
Terminal Length:
0.250 inches
Body Diameter:
0.125 inches
Body Length:
0.468 inches
Schematic Diagram Designator:
Electrod (s) grounded to case
Mounting Facility Screw Thread Series Designator:
Unf
Mounting Facility Type And Quantity:
1 threaded bushing
Capacitance Value Per Section:
1000.000 picofarads single section
Voltage Tempurature Limits Per Section In Percent Capacitance Change:
-22.0/+22.0 with rated voltage applied single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Thread Size:
0.216 inches
Nonderated Continuous Voltage Rating And Type Per Section:
500.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
-20.00/+20.00 percent single section
-20.00/+20.00 percent single section Case Material:
-20.00/+20.00 percent single section Case Material: Metal
-20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp:
-20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 7500.0 megohms
-20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 7500.0 megohms Power Factor At Reference Tempurature In Percent:
-20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 7500.0 megohms Power Factor At Reference Tempurature In Percent: 2.5000
-20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 7500.0 megohms Power Factor At Reference Tempurature In Percent: 2.5000 Terminal Surface Treatment:

N/a

Shelf Life:

NSN 5910-00-754-7116

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0