

View Online at <https://aerobasegroup.com/nsn/5910-00-754-7186>

Body Style:

W/thd mtg hole/stud, terminal (s) on one end

Reliability Indicator:

Not established

Width Across Flats:

0.250 inches

Terminal Length:

0.223 inches

Body Diameter:

0.250 inches

Body Length:

0.171 inches

Terminal Diameter:

0.040 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

1 threaded bushing

Insulation Resistance At Maximum Operating Temp:

3000.0 megohms

Capacitance Value Per Section:

82.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 with rated voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.099 inches

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Range Per Section:

-4.10/+4.10 picofarads single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

40000.0 megohms

Quality Factor At Reference Temp:

20.0000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

1 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0