## NSN 5910-00-754-7186

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-754-7186
Body Style:
W/thd mtg hole/stud, terminal (s) on one end
Reliability Indicator:
Not established
Width Across Flats:
0.250 inches
Terminal Length:
0.223 inches
Body Diameter:
0.250 inches
Body Length:
0.171 inches
Terminal Diameter:
0.040 inches
Schematic Diagram Designator:
Electrod (s) grounded to case
Mounting Facility Screw Thread Series Designator:
Unf
Mounting Facility Type And Quantity:
1 threaded bushing
Insulation Resistance At Maximum Operating Temp:
3000.0 megohms
Capacitance Value Per Section:
82.000 picofarads single section
Voltage Tempurature Limits Per Section In Percent Capacitance Change:
-15.0/+15.0 with rated voltage applied single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Thread Size:
0.099 inches
Nonderated Continuous Voltage Rating And Type Per Section:
500.0 dc single section
Tolerance Range Per Section:
-4.10/+4.10 picofarads single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
40000.0 megohms
Quality Factor At Reference Temp:
20.0000

Solder

**Terminal Surface Treatment:** 

## NSN 5910-00-754-7186

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Terminal Type And	Quantity:
-------------------	-----------

1 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0