

View Online at https://aerobasegroup.com/nsn/5910-00-754-8615

## Body Style:

W/o mtg facilities, radial terminals

## **Reliability Indicator:**

Not established

# Body Diameter:

0.220 inches

#### Body Length:

0.430 inches

#### **Terminal Height From Body:**

1.250 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## Insulation Resistance At Maximum Operating Temp:

1000.0 megohms

#### Capacitance Value Per Section:

51.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

## Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

## Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-60.0/+60.0 single section

## **Tolerance Range Per Section:**

-2.00/+2.00 percent single section

#### Case Material:

Ceramic

Insulation Resistance At Reference Temp:

50000.0 megohms

## Quality Factor At Reference Temp:

1000.0000

## **Terminal Surface Treatment:**

Solder

## Test Data Document:

81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 uninsulated wire lead

#### Shelf Life:

N/a

Unit Of Measure:



Demilitarization:

No

Fiig:

A010b0