NSN 5910-00-755-4392

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-755-4392			
Body Style:			
W/thd bushing mtg, terminals on opposite ends			
Reliability Indicator:			
Not established			
Terminal Length:			
1.625 inches			
Body Diameter:			
0.400 inches			
Body Length:			
0.833 inches			
Body Width:			
0.400 inches			
Body Height:			
0.400 inches			
Schematic Diagram Designator:			
Electrod (s) grounded to case, w/gnd terminal			
Internal Electrical Connection Type:			
Extended foil			
Mounting Facility Screw Thread Series Designator:			
Unf			
Mounting Facility Type And Quantity:			
1 threaded bushing			
Features Provided:			
Mounting hardware and hermetically sealed case			
Insulation Resistance At Maximum Operating Temp:			
150.0 megohms			
Capacitance Value Per Section:			
12000.000 picofarads single section			
Nonderated Operating Temp:			
Between -55.0 degrees celsius and 125.0 degrees celsius			
Thread Size:			
0.312 inches			
Nonderated Continuous Voltage Rating And Type Per Section:			
400.0 dc single section			
Tolerance Range Per Section:			
-10.00 to 10.00 percent single section			
Case Material:			
Metal			

Insulation Resistance At Reference Temp:

18000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

1.0000

NSN 5910-00-755-4392

Paper Dielectric Fixed Capacitor - Page 2 of 2



		T 4 4
ı ermına	i Surtace	Treatment:

Solder

Test Data Document:

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0