

View Online at <https://aerobasegroup.com/nsn/5910-00-758-6156>

Thread Class:

2a

Body Style:

Piston

Overall Length:

0.469 inches

Terminal Length:

0.109 inches

Bushing Diameter:

0.234 inches

Bushing Length:

0.188 inches

Body Length:

0.281 inches

Overall Diameter:

0.281 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Terminal Diameter:

0.094 inches

Quality Factor At 25 Deg Celsius:

2000.0

Fragility Factor:

Moderately rugged

Mounting Facility Screw Thread Series Designator:

Uns

Inclosure Type:

Encased

Terminal Location:

One side perpendicular

Tuning Characteristic:

Straight line capacity single section

Adjustment Device Rotation:

10.0 turns clockwise

Bushing Shape:

Round

Insulation Dc Resistance At 25 Deg Celsius:

10000.0 gigohms

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

64

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.234 inches

Capacitance Range In Picofarads:

+0.8/+10.0 single section

Nonderated Voltage Rating And Type:

250.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.01 single section

Precious Material And Location:

Metal surfaces gold

Precious Material:

Gold

Supplementary Features:

18jan01 item reviewed under girder project. Zn non-concur cancellation action

Terminal Type And Quantity:

1 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0