

View Online at <https://aerobasegroup.com/nsn/5910-00-758-6156>

**Thread Class:**

2a

**Body Style:**

Piston

**Overall Length:**

0.469 inches

**Terminal Length:**

0.109 inches

**Bushing Diameter:**

0.234 inches

**Bushing Length:**

0.188 inches

**Body Length:**

0.281 inches

**Overall Diameter:**

0.281 inches

**Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:**

0.0 single section

**Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Terminal Diameter:**

0.094 inches

**Quality Factor At 25 Deg Celsius:**

2000.0

**Fragility Factor:**

Moderately rugged

**Mounting Facility Screw Thread Series Designator:**

Uns

**Inclosure Type:**

Encased

**Terminal Location:**

One side perpendicular

**Tuning Characteristic:**

Straight line capacity single section

**Adjustment Device Rotation:**

10.0 turns clockwise

**Bushing Shape:**

Round

**Insulation Dc Resistance At 25 Deg Celsius:**

10000.0 gigohms

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Thready Qty Per Inch (tpi):**

64

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thread Size:**

0.234 inches

**Capacitance Range In Picofarads:**

+0.8/+10.0 single section

**Nonderated Voltage Rating And Type:**

250.0 dc continuous single section

**Adjustment Device Drive Type And Quantity:**

1 slotted screw

**Capacitance Drift In Picofarads:**

0.01 single section

**Precious Material And Location:**

Metal surfaces gold

**Precious Material:**

Gold

**Supplementary Features:**

18jan01 item reviewed under girder project. Zn non-concur cancellation action

**Terminal Type And Quantity:**

1 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A096a0