

View Online at https://aerobasegroup.com/nsn/5910-00-760-3268

Plastic Dielectric Fixed Capacitor - Page 1 of 2

### **Body Style:**

W/o mtg facilities terminal (s) on one surface

#### **Reliability Indicator:**

Not established

# **Terminal Length:**

1.125 inches

### **Body Length:**

0.930 inches

#### **Body Width:**

0.312 inches

#### **Body Height:**

#### 0.100 inches

### Center To Center Distance Between Terminals Parallel To Length:

0.700 inches

#### **Terminal Diameter:**

0.020 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

0.003 microfarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-190.0 single section

### Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

### Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

#### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Plastic

# Insulation Resistance At Reference Temp:

10000000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.0200

# **Terminal Surface Treatment:**

Solder

# **Terminal Type And Quantity:**

2 uninsulated wire lead

### Shelf Life:

N/a

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0