## NSN 5910-00-760-7522

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-760-7522

| Pady Styles  |
|--|
| Body Style:  |
| W/mtg tabs/flanges, terminals on opposite surfaces                           |
| Reliability Indicator:   |
| Not established  Town in all a partle  |
| Terminal Length:   |
| 0.312 inches   |
| Body Length:   |
| 1.750 inches   |
| Body Width:  |
| 1.000 inches   |
| Body Height:   |
| 0.750 inches   |
| Unthreaded Mounting Hole Diameter:   |
| 0.188 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 2.125 inches   |
| Schematic Diagram Designator:  |
| No common or grounded electrode (s)  |
| Mounting Facility Type And Quantity:   |
| 2 unthreaded mounting holes  |
| Features Provided:   |
| Hermetically sealed case   |
| Capacitance Value Per Section:   |
| 5.000 microfarads single section   |
| Nonderated Operating Temp:   |
| Between -65.0 degrees celsius and 125.0 degrees celsius                      |
| Nonderated Continuous Voltage Rating And Type Per Section:                   |
| 150.0 dc single section  |
| Tolerance Range Per Section:   |
| -2.00/+2.00 percent single section   |
| Case Material:   |
| Metal  |
| Terminal Type And Quantity:  |
| 2 tab, solder lug  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |

Fiig: A010b0