## NSN 5910-00-761-9162

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-761-9162 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 1.094 inches **Terminal Length:** 0.312 inches **Bushing Diameter:** Between 0.251 inches and 0.255 inches **Bushing Length:** 0.250 inches **Body Length:** 0.844 inches **Overall Diameter:** 0.312 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -50.0/+50.0 single section **Quality Factor At 25 Deg Celsius:** 500.0 **Mounting Facility Screw Thread Series Designator:** Unef **Inclosure Type:** Encased **Terminal Location:** Circumference on adjustment control end bent backward **Adjustment Device Torque:** Between 1.000 inch-ounces and 10.000 inch-ounces **Bushing Shape:** Round w/flat Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms **Bushing Width:** Between 0.230 inches and 0.234 inches **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): 32 **Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thread Size:** 

0.250 inches

## NSN 5910-00-761-9162

Glass Dielectric Variable Capacitor - Page 2 of 2



Cai	pacita	nce l	Rang	e In	Picof	farad	s:

+1.0/+14.0 single section

**Nonderated Voltage Rating And Type:** 

1000.0 dc continuous single section

**Adjustment Device Drive Type And Quantity:** 

1 hex socket

**Terminal Type And Quantity:** 

1 tab, solder lug and 1 turret

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A096a0