

View Online at <https://aerobasegroup.com/nsn/5910-00-763-3797>

Body Style:

Rotary

Body Length:

0.844 inches

Body Width:

0.656 inches

Body Height:

0.375 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

-1500.0 single section

Unthreaded Mounting Hole Diameter:

0.120 inches and 0.120 inches

Quality Factor At 25 Deg Celsius:

500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.438 inches

Inclosure Type:

Encapsulated

Adjustment Device Torque:

Between 4.000 inch-ounces and 20.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

10.0 gigohms

Mounting Facility Type And Quantity:

2 unthreaded hole

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Capacitance Range In Picofarads:

+11.0 to 110.0 single section

Nonderated Voltage Rating And Type:

500.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.50 single section

Test Data Document:

13499-917-1248-010 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0