

View Online at https://aerobasegroup.com/nsn/5910-00-764-0149

### Body Style:

W/o mtg facilities, axial terminals

### **Reliability Indicator:**

Not established

# Terminal Length:

1.250 inches

#### Body Diameter:

0.090 inches

**Body Length:** 

0.240 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### Capacitance Value Per Section:

### 330.000 picofarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-10.0/+2.0 with rated voltage applied single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

## Tolerance Range Per Section:

-10.00/+10.00 percent single section

#### Case Material:

Ceramic

## Insulation Resistance At Reference Temp:

100000.0 megohms

## Dissipation Factor At Reference Tempurature In Percent:

1.0000

## **Terminal Surface Treatment:**

Solder

## Test Data Document:

81349-milc11015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-milc11015-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### Terminal Type And Quantity:

2 uninsulated wire lead

### Shelf Life:

N/a

#### Unit Of Measure:

--

Demilitarization: