

View Online at https://aerobasegroup.com/nsn/5910-00-764-6640

## **Body Style:**

W/o mtg facilities, radial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.250 inches

### **Body Diameter:**

0.550 inches

**Body Length:** 

0.120 inches

### Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.315 inches and 0.435 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### **Capacitance Value Per Section:**

100.000 picofarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-80.0/+30.0 with rated voltage applied single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

1500.0 dc single section

## **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### **Case Material:**

Ceramic

### Insulation Resistance At Reference Temp:

200000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

1.000

**Terminal Surface Treatment:** 

Solder

### **Test Data Document:**

81349-mil-c-11015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

2 uninsulated wire lead

#### **Specification Data:**

81349-mil-c-11015/11 government specification

Shelf Life:

N/a

- Unit Of Measure:
- ---



Demilitarization:

No

Fiig:

A010b0