Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-766-6836

# **Body Style:**

W/o mtg facilities, terminal (s) on one surface

# **Reliability Indicator:**

Not established

# **Body Length:**

2.500 inches

### **Body Width:**

1.188 inches

### **Body Height:**

3.875 inches

### Center To Center Distance Between Terminals Parallel To Length:

1.125 inches

**Terminal Height From Body:** 

### 0.625 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

### **Features Provided:**

Hermetically sealed case

### Insulation Resistance At Maximum Operating Temp:

15.0 megohm-microfarads

# Capacitance Value Per Section:

4.000 microfarads single section

## Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

330.0 ac-rms single section and 600.0 dc single section

### **Tolerance Range Per Section:**

-6.00 to 6.00 percent single section

### **Case Material:**

Metal

### Insulation Resistance At Reference Temp:

4500.0 megohm-microfarads

# Power Factor At Reference Tempurature In Percent:

1.0000

# **Terminal Surface Treatment:**

Solder

### **Terminal Type And Quantity:**

2 standoff, solder lug

Shelf Life:

N/a

### Unit Of Measure:

---



Demilitarization:

No

Fiig:

A010b0