## NSN 5910-00-771-2650

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-771-2650

**Body Style:** 

W/o mtg facilities, terminal (s) on one surface

**Reliability Indicator:** 

Not established

Body Length:

3.750 inches

Body Width:

2.250 inches

Body Height:

3.875 inches

**Center To Center Distance Between Terminals Parallel To Length:** 

Between 1.813 inches and 2.063 inches

**Terminal Height From Body:** 

1.750 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Features Provided:** 

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:** 

15.0 megohm-microfarads

**Capacitance Value Per Section:** 

4.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

2000.0 dc single section

**Tolerance Range Per Section:** 

-10.00 to 10.00 percent single section

**Case Material:** 

Metal

Insulation Resistance At Reference Temp:

1500.0 megohm-microfarads

**Dissipation Factor At Reference Tempurature In Percent:** 

1.0000

**Terminal Surface Treatment:** 

Solder

**Test Data Document:** 

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 threaded stud

Shelf Life:

N/a

## NSN 5910-00-771-2650

Paper Dielectric Fixed Capacitor - Page 2 of 2



| ш | ın | 10 | <i>(</i> )+ | Measure: |  |
|---|----|----|-------------|----------|--|
|   |    |    |             |          |  |

--

Demilitarization:

No

Fiig:

A010b0