NSN 5910-00-772-5673

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-772-5673

view Offiline at https://defobasegroup.com/nsi//05/10-00-772-3073
Body Style:
W/thd hol (s)/stud(s), terminal(s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.875 inches
Body Length:
1.594 inches
Body Width:
2.000 inches
Body Height:
1.000 inches
Center To Center Distance Between Terminals Parallel To Length:
0.625 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.000 inches
Mounting Facility Screw Thread Series Designator:
Unc
Unc
Unc Mounting Facility Type And Quantity:
Unc Mounting Facility Type And Quantity: 2 threaded mounting studs
Unc Mounting Facility Type And Quantity: 2 threaded mounting studs Features Provided:
Unc Mounting Facility Type And Quantity: 2 threaded mounting studs Features Provided: Hermetically sealed case
Unc Mounting Facility Type And Quantity: 2 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section:
Unc Mounting Facility Type And Quantity: 2 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 1.150 microfarads single section
Unc Mounting Facility Type And Quantity: 2 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 1.150 microfarads single section Nonderated Operating Temp:
Unc Mounting Facility Type And Quantity: 2 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 1.150 microfarads single section Nonderated Operating Temp: 60.0 degrees celsius
Unc Mounting Facility Type And Quantity: 2 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 1.150 microfarads single section Nonderated Operating Temp: 60.0 degrees celsius Thread Size:
Unc Mounting Facility Type And Quantity: 2 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 1.150 microfarads single section Nonderated Operating Temp: 60.0 degrees celsius Thread Size: 0.138 inches
Unc Mounting Facility Type And Quantity: 2 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 1.150 microfarads single section Nonderated Operating Temp: 60.0 degrees celsius Thread Size: 0.138 inches Nonderated Continuous Voltage Rating And Type Per Section:
Mounting Facility Type And Quantity: 2 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 1.150 microfarads single section Nonderated Operating Temp: 60.0 degrees celsius Thread Size: 0.138 inches Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section
Mounting Facility Type And Quantity: 2 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 1.150 microfarads single section Nonderated Operating Temp: 60.0 degrees celsius Thread Size: 0.138 inches Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section:
Mounting Facility Type And Quantity: 2 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 1.150 microfarads single section Nonderated Operating Temp: 60.0 degrees celsius Thread Size: 0.138 inches Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section
Mounting Facility Type And Quantity: 2 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 1.150 microfarads single section Nonderated Operating Temp: 60.0 degrees celsius Thread Size: 0.138 inches Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material:
Mounting Facility Type And Quantity: 2 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 1.150 microfarads single section Nonderated Operating Temp: 60.0 degrees celsius Thread Size: 0.138 inches Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Metal

2 uninsulated wire lead

NSN 5910-00-772-5673

Paper Dielectric Fixed Capacitor - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0