NSN 5910-00-779-2713



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-779-2713 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 0.188 inches **Body Diameter:** 1.000 inches **Body Length:** 2.000 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.500 inches **Terminal Diameter:** 0.031 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Etched foil **Impedance At Minimum Operating Tempurature In Ohms:** 5.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 2000.000 microfarads single section **Nonderated Operating Temp:** Between -10.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 30.0 dc single section **Tolerance Range Per Section:** -10.00/+100.00 percent single section Case Material: **Plastic Capacitive Electrode Material:** Aluminum Dc Leakage At Reference Temp: 3.000 microamperes **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 uninsulated wire lead

Shelf Life: N/a

NSN 5910-00-779-2713

Electrolytic Fixed Capacitor - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0