NSN 5910-00-780-8539

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-780-8539

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
2.563 inches
Body Width:
1.063 inches
Body Height:
1.688 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
1.600 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section
600.0 dc single section
600.0 dc single section Tolerance Range Per Section:
600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section
600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material:
600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic
600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp:
600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms
600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment:
600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder
600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity:
600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead
600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
600.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: