

View Online at https://aerobasegroup.com/nsn/5910-00-781-2273

## **Body Style:**

W/o mtg facilities, radial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.250 inches

### **Body Diameter:**

0.280 inches

**Body Length:** 

0.120 inches

### Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.190 inches and 0.310 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### **Capacitance Value Per Section:**

15.000 picofarads single section

# Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-25.0/+15.0 with rated voltage applied single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Ceramic

#### Insulation Resistance At Reference Temp:

200000.0 megohms

#### **Dissipation Factor At Reference Tempurature In Percent:**

1.500

# **Terminal Surface Treatment:**

Solder

# **Test Data Document:**

81349-mil-c-11015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

2 uninsulated wire lead

#### **Specification Data:**

81349-mil-c-11015/9 government specification

Shelf Life:

N/a

- Unit Of Measure:
- ---



Demilitarization:

No

Fiig:

A010b0