Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-782-1975

## **Body Style:**

W/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not established

## **Terminal Length:**

1.500 inches

#### **Body Diameter:**

0.289 inches

#### **Body Length:**

0.822 inches

#### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

#### Anode Type:

Solid

#### **Electrical Polarization:**

Polarized

#### **Features Provided:**

Hermetically sealed case

## **Capacitance Value Per Section:**

10.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Dc Leakage At Maximum Operating Temp:

40.0 milliamperes

## Nonderated Continuous Voltage Rating And Type Per Section:

35.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Metal

#### **Capacitive Electrode Material:**

Tantalum

## **Dissipation Factor At Reference Tempurature In Percent:**

6.0000

#### Dc Leakage At Reference Temp:

4.000 microamperes

## **Terminal Surface Treatment:**

Solder

## **Test Data Document:**

81349-mil-c-26655 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

# NSN 5910-00-782-1975

Electrolytic Fixed Capacitor - Page 2 of 2

AeroBase Group

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0