## NSN 5910-00-782-4759

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-782-4759 **Body Style:** W/o mtg facilities, radial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Diameter:** 0.945 inches **Body Length:** 0.265 inches **Center To Center Distance Between Terminals Parallel To Diameter:** Between 0.469 inches and 0.531 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 5000.0 megohms **Capacitance Value Per Section:** 2000.000 picofarads single section Voltage Tempurature Limits Per Section In Percent Capacitance Change: -92.0/+22.0 with rated voltage applied single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 6000.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 10000.0 megohms **Terminal Surface Treatment:** Solder **Test Data Document:** 97942-578r778 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5910-00-782-4759

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0