## NSN 5910-00-782-7718

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-782-7718 **Body Style:** W/mtg bracket, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.625 inches **Body Diameter:** 0.750 inches **Body Length:** 2.125 inches **Unthreaded Mounting Hole Diameter:** 0.156 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Mounting Facility Type And Quantity:** 1 unthreaded mounting holes **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 40000.0 megohms **Capacitance Value Per Section:** 0.220 microfarads single section **Nonderated Operating Temp:** Between -65.0 degrees celsius and 65.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section Case Material: Metal **Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.1000 **Terminal Surface Treatment:** Solder **Dielectric Material:** 

Plastic polyethylene terephthalate

**Case Insulation Material:** 

**Plastic** 

## NSN 5910-00-782-7718

Plastic Dielectric Fixed Capacitor - Page 2 of 2



## **Test Data Document:**

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

٠,	uninsi	nateli	\\/Ir\	hcal
_	ummo	JIALEU	wiic	ıcau

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A010b0