Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-783-6247

## **Body Style:**

W/thd mtg hol (s)/stud(s) terminal(s) on one surface

## **Reliability Indicator:**

Not established

## **Body Length:**

1.406 inches

#### **Body Width:**

0.766 inches

## **Body Height:**

1.688 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.562 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

## Mounting Facility Screw Thread Series Designator:

Unc

## Mounting Facility Type And Quantity:

2 threaded mounting studs

## **Features Provided:**

Mounting hardware and hermetically sealed case

# Capacitance Value Per Section:

2.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### **Thread Size:**

0.138 inches

## Nonderated Continuous Voltage Rating And Type Per Section:

26.0 ac-rms single section

## **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

#### **Case Material:**

Metal

# Insulation Resistance At Reference Temp:

753.0 megohms

# Power Factor At Reference Tempurature In Percent:

1.0000

# **Terminal Surface Treatment:**

Solder

## **Terminal Type And Quantity:**

2 tab, solder lug

### **Reference Number Differentiating Characteristics:**

As differentiated by quality control for polaris

Paper Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0