

View Online at https://aerobasegroup.com/nsn/5910-00-784-0927

Body Style:

W/o mtg facilities, radial terminals

Reliability Indicator:

Not established

Terminal Length:

1.250 inches

Body Diameter:

0.266 inches

Body Length:

0.125 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.200 inches

Terminal Diameter:

0.020 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Ticonderoga class cg (47); sturgeon class ssn (637); radar, series an/sps-4 (v); los angeles class ssn (688); missile, all-weather antiship, harpoon (agm-84); support equipment, b-1 aircraft; virginia class cgn (41); missile, air-to-air, phoenix (aim-54); engine, aircraft,

f100-pw-200 (f-16a/b/c/d)

Capacitance Value Per Section:

1000.000 picofarads single section

Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-33.0/+85.0 with rated voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

600.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Ceramic

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5910-00-784-0927 Ceramic Dielectric Fixed Capacitor - Page 2 of 2

Fiig: A010b0

