NSN 5910-00-785-1722

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/psn/5010-00-785-1722

View Online at https://aerobasegroup.com/nsn/5910-00-785-1722
Body Style:
W/mtg bracket, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Diameter:
0.562 inches
Body Length:
1.124 inches
Unthreaded Mounting Hole Diameter:
0.156 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Mounting Facility Type And Quantity:
2 unthreaded mounting holes
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
5.0 megohm-microfarads
Capacitance Value Per Section:
0.150 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
600.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
2000.0 megohm-microfarads
Power Factor At Reference Tempurature In Percent:
1.5000
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:

N/a

NSN 5910-00-785-1722

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0