NSN 5910-00-786-8787

Quartz Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-786-8787

Body Style:
Piston
Overall Length:
0.748 inches
Shaft Length:
0.186 inches single shaft
Body Length:
0.562 inches
Overall Diameter:
0.312 inches
Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:
+0.0/+50.0 single section
Center To Center Distance Between Terminals Parallel To Length:
0.438 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.281 inches
Quality Factor At 25 Deg Celsius:
1500.0
Inclosure Type:
Encased
Adjustment Device Torque:
Between 1.000 inch-ounces and 10.000 inch-ounces
Insulation Dc Resistance At 25 Deg Celsius:
100.0 gigohms
Mounting Facility Type And Quantity:
4 terminal
Nonderated Operating Temp:
Between -55.0 degrees celsius and 150.0 degrees celsius
Shaft Type:
Round, slotted single shaft
Capacitance Range In Picofarads:
+0.6/+5.5 single section
Nonderated Voltage Rating And Type:
750.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 shaft
Capacitance Drift In Picofarads:
0.01 single section
Test Data Document:
81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

4 wire lead

Terminal Type And Quantity:

NSN 5910-00-786-8787

Quartz Dielectric Variable Capacitor - Page 2 of 2



Shelf	Life:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0