## NSN 5910-00-788-8670

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-788-8670

Body	Style:
------	--------

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

Between 1.625 inches and 2.625 inches

**Body Diameter:** 

Between 0.745 inches and 0.765 inches

**Body Length:** 

Between 2.219 inches and 2.281 inches

**Terminal Diameter:** 

0.032 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Features Provided:** 

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:** 

10.0 megohm-microfarads

**Capacitance Value Per Section:** 

10.000 microfarads single section

**Nonderated Operating Temp:** 

Between -40.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

**Tolerance Range Per Section:** 

-20.00/+20.00 percent single section

**Case Material:** 

Metal

**Insulation Resistance At Reference Temp:** 

200.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

1.000

**Terminal Surface Treatment:** 

Solder

**Dielectric Material:** 

Paper

**Case Insulation Material:** 

Plastic

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-00-788-8670

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0