

View Online at <https://aerobasegroup.com/nsn/5910-00-792-2568>

**Reliability Indicator:**

Not established

**Schematic Diagram Designator:**

Electrod (s) grounded to case, w/gnd terminal

**Anode Type:**

Etched foil

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

450.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

17.5 milliamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Criticality Code Justification:**

Test

**Tolerance Range Per Section:**

-15.00/+50.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Tantalum

**Dc Leakage At Reference Temp:**

1.800 microamperes

**Terminal Surface Treatment:**

Solder

**Special Features:**

Plate-mounting with two 90 diameter holes 1.360 by 1.300 inches center to center

**Test Data Document:**

81205-29-30666 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0