## NSN 5910-00-799-3594

pper-plastic Diplectric Metallized Fixed Canacitor - Page 1 of 2



Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5910-00-799-3594	
Body Style:	
W/thd mtg studs, axial terminals	
Reliability Indicator:	
Not established	
Terminal Length:	
0.296 inches	
Body Diameter:	
1.000 inches	
Body Length:	
1.875 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:	
1.125 inches	
Schematic Diagram Designator:	
No common or grounded electrode (s)	
Mounting Facility Screw Thread Series Designator:	
Unc	
Mounting Facility Type And Quantity:	
2 threaded mounting studs	
Insulation Resistance At Maximum Operating Temp:	
10.0 megohm-microfarads	
Capacitance Value Per Section:	
8.000 microfarads single section	
Nonderated Operating Temp:	
Between -55.0 degrees celsius and 125.0 degrees celsius	
Thread Size:	
0.138 inches	
Nonderated Continuous Voltage Rating And Type Per Section:	
200.0 dc single section	
Tolerance Range Per Section:	
-5 00/+5 00 percent single section	

Case Material:

Metal

Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

**Power Factor At Reference Tempurature In Percent:** 

1.0000

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 tab, solder lug

Shelf Life:

N/a

## NSN 5910-00-799-3594

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0