

View Online at <https://aerobasegroup.com/nsn/5910-00-801-5646>

Body Style:

W/o mtg facilities, radial terminals

Reliability Indicator:

Not established

Terminal Length:

1.500 inches

Body Diameter:

0.875 inches

Body Length:

0.219 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.375 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Pforrestal class cv; general purpose electronic test equipment gpete; submarine auxillary and miscellaneous systems; submarine surveillance systems; iwo jima class lph; trident hull structure; sturgeon class ssn (637)

Capacitance Value Per Section:

470.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-56.0/+22.0 without voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

6000.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

1000.0 megohms

Power Factor At Reference Temperature In Percent:

1.5000

Terminal Surface Treatment:

Solder

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0