NSN 5910-00-802-7432

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



1/5910-00-802-7432

Octamic Diciectife Lixed Capacitor
View Online at https://aerobasegroup.com/nsn/
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Unable To Decode:
Unable to decode and unable to decode
Terminal Length:
0.235 inches
Unable To Decode:
Unable to decode and unable to decode
Unable To Decode:
Unable to decode and unable to decode
Body Diameter:
Between 0.266 inches and 0.296 inches
Body Length:
Between 0.156 inches and 0.216 inches
Terminal Diameter:
0.062 inches
Schematic Diagram Designator:
Feedthrough
Capacitance Value Per Section:
0.001 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degre
Nonderated Continuous Voltage Rating And
500.0 dc single section

ees celsius

d Type Per Section:

500.0 dc single section

Tolerance Range Per Section:

-0.00 to 100.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

100000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

2.000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

1 solder stud and 1 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

NSN 5910-00-802-7432

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0