

View Online at https://aerobasegroup.com/nsn/5910-00-802-9385

## **Body Style:**

W/mtg bracket, axial terminals

**Reliability Indicator:** 

Not established

# **Terminal Length:**

1.625 inches

#### **Body Diameter:**

0.400 inches

#### **Body Length:**

1.375 inches

### **Unthreaded Mounting Hole Diameter:**

0.144 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

### Internal Electrical Connection Type:

Inserted tab

### Mounting Facility Type And Quantity:

1 unthreaded mounting holes

### **Features Provided:**

Hermetically sealed case

# Insulation Resistance At Maximum Operating Temp:

10.0 megohm-microfarads

## Capacitance Value Per Section:

0.220 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

#### **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

#### **Case Material:**

Metal

# Insulation Resistance At Reference Temp:

18000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

1.0000

# **Terminal Surface Treatment:**

Solder

#### **Test Data Document:**

81349-mil-c-25/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

Paper Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0