## NSN 5910-00-806-8261

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-806-8261

| 3   |
|---|
| Body Style:   |
| W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw |
| Reliability Indicator:  |
| Not establishednot established  |
| Terminal Length:  |
| 1.500 inches  |
| Body Diameter:  |
| 0.570 inches  |
| Body Length:  |
| 0.166 inches  |
| Schematic Diagram Designator:   |
| No common or grounded electrode (s)   |
| Capacitance Value Per Section:  |
| 39.000 picofarads single section  |
| Nonderated Operating Temp:  |
| Between -55.0 degrees celsius and 105.0 degrees celsius   |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:                                    |
| -75.0 single section  |
| Nonderated Continuous Voltage Rating And Type Per Section:  |
| 1000.0 dc single section  |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:                                      |
| -30.0/+30.0 single section  |
| Tolerance Range Per Section:  |
| -5.00/+5.00 percent single section  |
| Case Material:  |
| Ceramic   |
| Power Factor At Reference Tempurature In Percent:   |
| 0.1000  |
| Terminal Surface Treatment:   |
| Solder  |
| Terminal Type And Quantity:   |
| 2 uninsulated wire lead   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |

A010b0