NSN 5910-00-808-0558

Body Style:

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-808-0558

| W/thd bushing mtg, terminal (s) on one end |
|--|
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.625 inches |
| Body Diameter: |
| 1.000 inches |
| Body Length: |
| 2.312 inches |
| Schematic Diagram Designator: |
| Electrod (s) grounded to case |
| Mounting Facility Screw Thread Series Designator: |
| Unf |
| Mounting Facility Type And Quantity: |
| 1 threaded bushing |
| Features Provided: |
| Hermetically sealed case |
| Insulation Resistance At Maximum Operating Temp: |
| 5.0 megohm-microfarads |
| Capacitance Value Per Section: |
| 2.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Thread Size: |
| 0.312 inches |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 600.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Metal |
| Insulation Resistance At Reference Temp: |
| 2000.0 megohm-microfarads |
| Power Factor At Reference Tempurature In Percent: |
| 1.5000 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 1 tab, solder lug |
| Shelf Life: |
| N/a |

NSN 5910-00-808-0558

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| | | • - | | | | | | |
|---|----|------|------|----|----|-----|------|---|
| ш | ın | ıt (| r 1t | ΝЛ | മാ | CI. | ıre: | • |
| | | | | | | | | |

--

Demilitarization:

No

Fiig:

A010b0